5 zones mixer amplifier with MP3


MG-1060FU/1080FU/1120FU/1200FU
MG-1300FU/1400FU/1500FU/1650FU



MG-1060FU/1080FU/1120FU/1200FU
MG-1300FU/1400FU/1500FU/1650FU Front Panel——


Products characteristics

- Two channels signal input,Two lines signal input,one line signal output,
- 4--16 Ω Fixed resistance output, 70V/100V Level pressure output,
- Microphone 1 input priority,
- The output of overheating,overload,short circuit,alarm protection (The light will be opened)
- 5 zones with individual volume control output
- Mute function



MG-1060FU/1080FU/1120FU/1200FU
MG-1300FU/1400FU/1500FU/1650FU Rear Panel——

Connection way



Specifications:

Model NO	MG-1060FU	MG-1080FU	MG-1120FU	MG-1200 FU	MG-1300FU	MG-1400FU	MG-1500FU	MG-1650FU
Rated power output	60W	80W	120W	200W	300W	400W	500W	650W
Mode of output	4--16Ω , 70V/100V							
AUX output	600Ω 1V（0db）							
Input	MIC1.2 :600Ω 2.0--4.0MV, AUX1,2:15KΩ 775MV imbalance							
Frequency response	80Hz-16KHz (±3db)							
Harmonic distortion	Less than 0.1% at MIC1and 2:66dB. Aux1and 2:70dB							
SNR	Microphone1and 2:66dB Aux1and 2:70dB							
Protection	Overheating, overload,short circuit							
Mute function	MIC 1 signal controls other input signals							
Tone adjustment	Woofer:±10dB at 100 Hz, tweeter:±10dB at 15KHz							
Power supply	AC 220V-240V/50-60Hz							
Power dissipation	90W	120W	180W	280W	430W	580W	700W	900W
Gross weight	6.48KG	6.98KG	7.64KG	8.06KG	9.50KG	10.5KG	10.8KG	
Net weight	5.44KG	5.95KG	6.59KG	6.99KG	8.51KG	9.54KG	9.69KG	
Product dimension	MG-1060FU/1080FU/1120FU/1200FU/1300FU/1400FU/1500FU :483x86x86mm						MG-1650FU: 483X370X90MM	
Packing dimension	MG-1060FU/1080FU/1120FU/1200FU/1300FU/1400FU/1500FU : 540X410X170MM(1PC)						MG-1650FU: 545X490X170MM(1PC)	